

Electronic HID Ballast

for MH-HPS Lamps 400W



Features

- Small size / low weight
- Wireless control with Eco-Shift software (On/Off, dimming and status)
- Powers 400W MH and HPS lamps
- Also available: 250W, 320W and 350W
- Low THD
- Power Factor Correction included
- High efficiency
- Limited inrush current
- 20 min output Hold High
- 60 min output shutdown (no lamp current detected)
- Up to 9 m cable between driver and lamp
- Lamp power reduction at low line input
- 3-5 minute re-strike time
- Housing IP65 also available
- 1-10V analogue dimming input also available

Applications

- Industrial
- Retail
- Warehouse
- Public Buildings
- Greenhouse
- Sport Arenas
- Animal Stables

Tel. 519-650-9506
Fax 519-576-3169

www.eco-shiftpower.com

Eco-Shift Power Corporation
125 McGovern Rd.
Cambridge, Ontario
N3H 4R7

Technical Data

Specifications subject to change without notice

Input	187 - 305 Vrms
Input line freq.	47 - 63 Hz
Input current	2.1A max. at 200Vrms
PF	0.98 at 400W-200Vrms
Current THD	< 7% typ. full load, Unom

Output	115 - 200 Vrms typical
Switching freq.	>120 KHz-400 W out
Current nom.	4.5A max.
Run-up/short	< 1.8 x Inom
Ignition	3000 Vp
Crest factor	< 1.5, max. load
Regulation	± 1%

Dimming	Wireless control 50-100% output power
----------------	--

Efficiency	> 94%, max. load
-------------------	------------------

Protections	open output / output short / output over voltage / thermal / lamp end of life, rectification
--------------------	---

Mounting position	vertical
--------------------------	----------

Operating temp.	-40 to +50 C Tc: 65 C
------------------------	--------------------------

Storage temp	-40 to +85 C
---------------------	--------------

Approvals	CE / cUL / FCC
------------------	----------------

Dimensions	179 x 92.5 x 258
-------------------	------------------

Weight	2,8 kg IP20
---------------	----------------

Housing	Aluminium
----------------	-----------

Connectors	main: 3P wieland gesis male lamp: 3P wieland gesis female
-------------------	--

RF Frequency	2.4Ghz.
---------------------	---------